



| CODE | DESCRIPTION | WIDTH (W) | DEPTH (X) | HEIGHT (Y) | HEADROOM (Z) | WEIGHT (APPROX) |
|----------------|--|-----------|-----------|------------|--------------|-----------------|
| TSMT_SA | Single MAN-TRAP manual security booth (A) | 800 | 700 | 2 300 | 2 100 | 250 kg |
| TSMT_SB | Single MAN-TRAP manual security booth (B) | 900 | 900 | 2 300 | 2 100 | 280 kg |
| TSMT_SC | Single MAN-TRAP manual security booth (C) | 1 000 | 1 400 | 2 300 | 2 100 | 390 kg |
| TSMT_DA | Double MAN-TRAP manual security booth (A) | 1 550 | 700 | 2 300 | 2 100 | 480 kg |
| TSMT_DB | Double MAN-TRAP manual security booth (B) | 1 750 | 900 | 2 300 | 2 100 | 520 kg |
| TSMT_DC | Double MAN-TRAP manual security booth (C) | 1 950 | 1 400 | 2 300 | 2 100 | 700 kg |

Note: All dimensions are in millimetres (mm)

SPECIFICATION FOR ARCHITECTS AND SPECIFIERS

MAN-TRAP manual security booth (CODE as per above table), of powder coated mild steel (structured black) / 304 grade brushed stainless steel, including CBL 01/2/3/4/5/6/7 controller, fixed to level floor by means of four M12 x 90 counter sunk anchor bolts.

Due to our policy of continuous improvement, products are subject to change without notice. Custom designs are available on request.